

Competence creates Confidence.



● Model no. 1663/1669

RING STIFFNESS TESTERS

With the model 1663 and 1669 testers, the ring stiffness, ring flexibility and creep behaviour of thermoplastic pipes can be determined.

ISO 9967

ISO 9969

ISO 13968

DIN 16961

ASTM D 2412

Ring stiffness
Ring flexibility
Creep behaviour



Ensuring pipe integrity and performance

The devices have large compression plates which can be used to carry out the test on pipes of a large range of diameters and with a length of up to one meter.

A PC-based control software system provides clear visualisation of the device and enables convenient operation. In order to carry out the tests, the device provides various operating modes which can be used to exert either a constant force on the sample or to be able to move the compression plates at a constant speed. During this, the supplied or resulting forces and distances are recorded and the relevant force-distance diagrams created.

Deformation of the pipe at the external or internal diameters can be measured and recorded using a measuring trolley.

The interface to IPTDataLogging® 6 enables the long-term storage of the results and enables standard-compliant test reports to be created.



● Model no. 1663



● Model no. 1669

Standard features

- Fully automatic test procedure
- Testers specially developed for testing the ring stiffness, ring flexibility and creep behaviour
- Continuous force measurement and recording
- Convenient operation and clear visualisation via user interface (PC)
- Continuous measurement and recording of the deformation occurring to the external and internal diameters of the pipe
- CE conformity

Options

- Data input, evaluation and documentation of test data through IPTDataLogging software (PC)

RING STIFFNESS TESTERS



Design

		V1663-0005	V1669-0003
Max. test force	kN	25	60
Max. pipe diameter (outer)	mm	800	1,600
Adjustable preload up to max. force		Up to max. force	
Accuracy	%	± 1 of measurement between 0.40 kN and 25 kN	± 1 of measurement between 0.40 kN and 60 kN
Measuring accuracy of deformation of the internal diameter	%	1% of change or 0.1 mm (max. value is valid)	
Measuring range of distance measurement	mm	Min. 70 Max. 1,000	Min. 70 Max. 1,000
Compression plate travel	mm	930	1,630
Extensometer		Integrated	Mobile
Compatible with IPTDataLogging®		From version 5.x	
Permissible ambient temperature	°C	+5 to +30	
Permissible relative humidity	%	Max. 70 non-condensing	
Device width x depth x height	mm	2,550 x 1,155 x 1,950	2,500 x 1,710 x 2,635
Width of extensometer	mm	3,350 (extended)	1,820
Depth of extensometer	mm	-	700
Height of extensometer	mm	-	2,540
Weight (incl. extensometer)	t	Approx. 1.75	Approx. 3.0
Voltage data		230/400 V 50/60 Hz special voltages on request	